## (19) World Intellectual Property Organization International Bureau



## 

(43) International Publication Date 1 September 2005 (01.09.2005)

**PCT** 

## (10) International Publication Number WO 2005/080072 A1

(51) International Patent Classification<sup>7</sup>: B31C 3/04, 11/00

(21) International Application Number:

PCT/IT2005/000046

(22) International Filing Date: 1 February 2005 (01.02.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: FI2004A000046 24 February 2004 (24.02.2004) IT

(71) Applicant and

(72) Inventor: PERINI, Fabio [IT/IT]; Via S.Francesco, 1, I-55049 Viareggio\_(Lucca) (IT).

(74) Agent: MINCONE, Antimo; Studio Tecnico, Ing. Dr. Antimo Mincone, Via A. Manzoni 23, I-50121 Firenze (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (ΛΤ, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GΛ, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MACHINE AND METHOD FOR PRODUCING CARDBOARD TUBES



(57) Abstract: Method for producing cardboard tubes by winding a plurality of ribbons (U, L) onto a spindle (1), a preset number of said ribbons (U, L) being glued in correspondence of the lower surface thereof, characterized in that a predetermined amount of supplementary quick setting glue is applied on the lower surface of the last ribbon (U) destined to be wound on the spindle (1), in proximity to at least a longitudinal edge (BU) of said ribbon (U) forming a corresponding stripe of quick setting glue (G) astride of a section (ST) of the same ribbon interested by a subsequent cutting action executed downstream of the spindle (1).

